

FLOS

09.8312.DX Matte Rust

Oblique Qi NEW


Designed by Vincent Van Duysen, 2020

LED - Top LED - 8W - 525lm - 4000K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Base with Qi compatible wireless recharging system for mobile devices and wireless recharging cases for compatible devices. Driver input: 12 V

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Table
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	8
System power (W)	28
Source flux (lm)	827
System flux (lm)	525

Physical

Colour	Matte Rust
Orientation	Fixed
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions  PDF

Photometric Files

LDT / IES  ZIP

Technical Drawings


2D  ZIP

3D  ZIP

 Bim  ZIP

UK CA	IP 20	GWT 850°	IP 20
----------	----------	-------------	----------

Schematic light drawing



Beam Angle: 35°

h(m)	E(lx)	D(m)
1	252	2.18
2	63	4.36
3	28	6.54
4	16	8.72
5	10	10.90

Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	4000
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

Electrical

Insulation class	III
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No
Induction recharge QI	Yes
Charging socket/connector	USB-C