

FLOS

09.8311.DV Glossy Sage

Oblique Qi NEW



Designed by Vincent Van Duysen, 2020

LED - Top LED - 8W - 482lm - 3000K - CRI> 90 - Beam° 35

Professional table lamp with patented asymmetric optics. External power supply included with 1500-mm cable. USB-C connection integrated into the base of the device to recharge compatible devices. Base with Qi compatible wireless recharging system for mobile devices and wireless recharging cases for compatible devices. Driver input: 12 V

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Table
Environments	Indoor dry location
LED type	Top LED
Lamp category	LED
Number of heads	1
Power (W)	8
System power (W)	28
Source flux (lm)	760
System flux (lm)	482

Physical

Colour	Glossy Sage
Orientation	Fixed
Net weight (kg)	0.75
IP internal	20
IP external	20

Download

Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)

Technical Drawings


2D [↓ ZIP](#)

3D [↓ ZIP](#)

[Bim](#) [↓ ZIP](#)

UK CA	IP 20	GWT 850°	IP 20
----------	----------	-------------	----------

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Asymmetric
CCT (K)	3000
CRI>	90
LED Life / Failure Ratio	L90B10 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	35
Beam angle C90-270 (°)	46

Electrical

Insulation class	III
Driver	Remote included
Dimmable	Yes
Dimming type	Dimmable
Emergency type	No
Induction recharge QI	Yes
Charging socket/connector	USB-C