



# 186

## 1

### RECESSEDS

#### IP23 EXT



186.1

	QR-CBC 51		12V GU 5.3	Max. 50W	<b>1861</b>	<b>D</b>	<b>50</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>..</b>
	PAR 16		230V GU 10	Max. 50W	<b>1861</b>	<b>E</b>	<b>50</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>X</b>	<b>..</b>

#### LED CONTROL

	<b>N</b>	No Dimmable	186	.	<b>A</b>	<b>..</b>	<b>N</b>	.	.	.	.	<b>..</b>
	<b>C</b>	Dimmable IGBT / Triac	186	.	<b>A</b>	<b>..</b>	<b>C</b>	.	.	.	.	<b>..</b>
	<b>F</b>	Dimmable 1-10V / Push	186	.	<b>A</b>	<b>..</b>	<b>F</b>	.	.	.	.	<b>..</b>
	<b>D</b>	Dimmable Dali	186	.	<b>A</b>	<b>..</b>	<b>D</b>	.	.	.	.	<b>..</b>

#### LED COLOUR TEMPERATURE

	<b>3</b>	3000° K	186	.	<b>A</b>	<b>..</b>	.	.	<b>3</b>	.	.	<b>..</b>
	<b>4</b>	4000° K	186	.	<b>A</b>	<b>..</b>	.	.	<b>4</b>	.	.	<b>..</b>

#### LED BEAM ANGLE

	<b>4</b>	Medium	186	.	<b>A</b>	<b>..</b>	.	.	.	<b>4</b>	.	<b>..</b>
--	----------	--------	-----	---	----------	-----------	---	---	---	----------	---	-----------

#### LED COMPLEMENTS

	<b>B</b>	Clear Difusser	186	.	<b>A</b>	<b>..</b>	.	.	.	.	<b>B</b>	<b>..</b>
	<b>A</b>	Ice Difusser	186	.	<b>A</b>	<b>..</b>	.	.	.	.	<b>A</b>	<b>..</b>
	<b>O</b>	Opal Difusser	186	.	<b>A</b>	<b>..</b>	.	.	.	.	<b>O</b>	<b>..</b>

#### COLOURS

	<b>AB</b>	Aluminium + Black	186	.	.	<b>..</b>	.	.	.	.	.	<b>AB</b>
	<b>WB</b>	Satin White + Black	186	.	.	<b>..</b>	.	.	.	.	.	<b>WB</b>
	<b>BN</b>	Brushed Nickel + Black	186	.	.	<b>..</b>	.	.	.	.	.	<b>BN</b>
	<b>CB</b>	Chrome + Black	186	.	.	<b>..</b>	.	.	.	.	.	<b>CB</b>