

Cariddi 40 - 10° 3000K

Ernesto Gismondi



IP65

LUMINARIA

- Potencia (W): **40W**
- Tensión de alimentación: **220V-240 V**
- Flujo Luminoso (lm): **339lm**
- CCT: **3000K**
- Efficiency: **9%**
- Efficacy: **8.49lm/W**
- CRI: **90**

ESPECIFICACIONES

Monochromatic LED projector. Floor, wall, ceiling, eaves installation. Consists of an adjustable lighting unit and terminal board. Rotation on the base +/-180°, body tilting +/-130. Positioning is maintained by means of locking dowels. The base and the lighting unit are connected by a H05RN-F cable. EN AB47100 aluminium head and terminal board, EN AW6060 aluminium body, silicone gaskets. Electronic ballast integrated in the body. Silicone-sealed silk-screened tempered glass. Wiring to be performed inside the terminal board by piercing an IP65 grommet suitable for 8-12mm diameter cables. LED COB with PMMA lens and anodized aluminium reflector in 2 different beam versions. Available in 3 different powers. All the screws used outside the product are in AISI 316 stainless steel. All the components in die-cast aluminium are painted with 3-stage outdoor treatment: nanotechnologies, anti-oxidizing primer, polyester paint. Technical features of the light fixtures in compliance with EN60598-1 and section 2-5. IP Rating IP65 Insulation class I

CÓDIGO PRODUCTO: T418710W00

CARACTERÍSTICAS

- Código del artículo: **T418710W00**
- Color: **Gris anthracite**
- Instalación: **PieParedTecho**
- Material: **Aluminum, tempered glass, methacrylate**
- Serie: **Architectural Outdoor**
- diseño: **Ernesto Gismondi**

DIMENSIONES

- Longitud: **cm 25.6**
- Ancho: **cm 16.2**
- Altura: **cm 26**
- Diámetro: **cm 13.7**
- Resistencia al impacto: **IK07**
- Prueba calorífica: **750°**

FUENTES DE LUZ INCLUIDAS

- Categoría: **Led**
- Numero: **1**
- Potencia (W): **41W**
- Temperatura de Color (K): **3000K**
- CRI: **80**