LEDS C4

15-4968-21-14

V0


STRATA Plafón



Acabado
Cromo
Blanco mate

Material
Aluminio
Acero

IP23 3



CARACTERÍSTICAS TÉCNICAS

Fuente de luz
Fuente de luz: LED CREE
Potencia (W): 39W
Temperatura de color: Blanco cálido - 3000K
CRI: 80
Lumens nominales: 3700
Nº Leds: 3
Vida útil: 50.000h L70B30
Bin / Grup: 30H
MacAdam steps: 2 STEPS
Riesgo fotobiológico: RG1

EQUIPO
Marca: MEANWELL
Equipo incluido: Si, electrónico
Voltaje / Frecuencia: 220-240VAC/50-60Hz
Factor de potencia: 0.90
Protocolo de regulación: Corte de fase (LC)


Luminaria
Garantía: 2 Años

Logística
Eficiencia energética: LED A++
EAN: 8435381426835
Peso neto (Kg): 3.900
Peso en Kg (embalado): 5.745
Box: 505 x 195 x 500
Masterbox: 3

El acabado de la fotografía puede no coincidir con el de la referencia. Para identificar el real ver descripción del acabado.

■ AC Dimming Operation

◎ The following diagram depicts a typical installation utilizing the PCD-40 :




Under direct driving, the power supply will work in "constant current mode (CC)" and output voltage of the power supply will be clamped by sum of forward voltage (V_F) of the LED strip.

◎ Dimmer Compatibility Chart

Manufacturer	Dimmer Model	
LUTRON	SKYLARK SF-12P-277	(277VAC / 60Hz)
LUTRON	DVF-103P-277	(277VAC / 60Hz)
JUNG	Licht-Management 225 TDE	(230VAC / 50Hz)
JUNG	Licht-Management 225 NV DE	(230VAC / 50Hz)
BERKER	Tronic-Drehdimmer 286710	(230-240VAC / 50Hz)
CLIPSAL	32E450UDM	(220-240VAC / 50Hz)
CLIPSAL	NO 32E450TM	(220-240VAC / 50Hz)
CLIPSAL	NO 32E450LM	(220-240VAC / 50Hz)
CLIPSAL	Cat 400T	(230-240VAC / 50Hz)

Conduction angle: 30 degrees(min.) / 180 degrees(max.)



172
42
ø450
IRON/MATT WHITE
ø140
ø200
ø170
IRON/CHROME OR
MATT COOPER
273
220
30
5
ø10.5
10

11-12-2014


La Creu

IMC 15-4968


1




2




3




4




5




6









Dec/22/2014